

## Probes and accessories Temperature probes

Reference	Description	Family	Pack
<b>AKO-14901</b>	NTC probe, from -50 to 100°C, 1.5 m of cable	1590	48 Units
<b>AKO-14902</b>	NTC probe, from -50 to 100°C, 2.0 m of cable	1590	48 Units
<b>AKO-14903</b>	NTC probe, from -50 to 100°C, 3.0 m of cable	1590	48 Units
<b>AKO-14906</b>	NTC probe, from -50 to 100°C, 6.0 m of cable	1590	24 Units
<b>AKO-14915</b>	NTC probe, from -50 to 100°C, stainless steel connector, 3.0 m of cable	1590	1 Unit
<b>AKO-15561</b>	NTC probe, from -50 to 100°C, IP68 protection, AISI 304. 1.5 m of cable	1590	10 Units
<b>AKO-155801</b>	PTC probe, from -50 to 150°C, 1.5 m of cable	1590	10 Units
<b>AKO-155802</b>	PTC probe, from -50 to 150°C, 2.0 m of cable	1590	10 Units
<b>AKO-155803</b>	PTC probe, from -50 to 150°C, 3.0 m of cable	1590	10 Units
<b>AKO-155807</b>	PTC probe, from -50 to 150°C, 7.0 m of cable	1590	10 Units
<b>AKO-155815</b>	PTC probe, from -50 to 150°C, 15.0 m of cable	1590	5 Units
<b>AKO-155830</b>	PTC probe, from -50 to 150°C, 30.0 m of cable	1590	1 Unit
<b>AKO-15584</b>	Pt-100 probe, from -50 to 180°C, 10.0 m of cable without braid	1590	1 Unit
<b>AKO-15585A</b>	Pt-100 probe, from -50 to 180°C, 2.0 m of cable without braid	1590	1 Unit
<b>AKO-15595</b>	Pt-100 probe, from -50 to 200°C, 1.5 m of cable with braid	1590	5 Units
<b>AKO-15587</b>	Pt-100 probe, from -60 to 350°C, 2.0 m of cable with braid	1590	1 Unit
<b>AKO-15596</b>	Pt-100 probe, from -200 to 600°C, in bracket 100 x 230 mm	1590	1 Unit
<b>AKO-15597</b>	Pt-100 probe, from -100 to 200°C, 2.0 m of cable	1590	1 Unit
<b>AKO-15599</b>	Pt-100 probe to environment temperature	1590	1 Unit
<b>AKO-15601</b>	J type probe, from 0 to 600°C, 3.0 m of cable	1590	1 Unit
<b>AKO-15602</b>	K type probe, from 0 to 1.000°C, 3.0 m of cable	1590	1 Unit
<b>AKO-15586</b>	Communication cable RS485, 3x0,5 mm <sup>2</sup> shielded	1590	100 m (A)
<b>AKO-80008</b>	Pt-100 probe, EExd IIT6, IP65 box, to drums	1590	1 Unit
<b>AKO-80019</b>	Pt-100 probe, EExd IIT6, for Ex zone and pipes	1590	1 Unit
<b>AKO-15582</b>	Pt-100 probe, from -50 to 180°C, 2.0 m of cable without braid	1590	1 Unit

(A) The metres of packaged material are the standard ones; however, we reserve the right to supply in different lengths those indicated.

## Probes and accessories Humidity probes

**AKO-80040**



**AKO-80013**



Reference	Description	Family	Pack
<b>AKO-80013</b>	Wall humidity probe, 10 to 95%, -5/50°C, output 4-20mA	1590	1 Unit
<b>AKO-80040</b>	Tubular humidity probe, 5 to 95%, -10/70°C, output 4-20mA	1590	1 Unit