

Narzędzia CONTA-TOOL

Końcówki nieizolowane

Końcówki nieizolowane

	Przekrój po-		Długość usunięcia po- włoki izolacyjnej mm ²	Wymiary w mm			Ilość pak.	Typ	Nr kat.
	przecznym mm ²	AWG		A	B	C			
	0,25	24	5	5,0	0,75	1,7	1000	H 0,25/5	3096.0
	0,50	20	5	6,0	1,0	2,1	1000	H 0,5/6	2216.0
	0,50	20	10	10,0	1,0	2,1	1000	H 0,5/10	3097.0
	0,75	20	6	6,0	1,2	2,3	1000	H 0,75/6	2217.0
	0,75	20	10	10,0	1,2	2,3	1000	H 0,75/10	2218.0
	1,00	18	6	6,0	1,4	2,5	1000	H 1,0/6	2219.0
	1,00	18	10	10,0	1,4	2,5	1000	H 1,0/10	2220.0
	1,50	16	7	7,0	1,8	2,8	1000	H 1,5/7	2221.0
	1,50	16	10	10,0	1,8	2,8	1000	H 1,5/10	2222.0
	1,50	16	12	12,0	1,8	2,8	1000	H 1,5/12	3098.0
	1,50	16	18	18,0	1,8	2,8	1000	H 1,5/18	3099.0
	2,50	14	7	7,0	2,2	3,4	1000	H 2,5/7	2223.0
	2,50	14	10	10,0	2,2	3,4	1000	H 2,5/10	3100.0
	2,50	14	12	12,0	2,2	3,4	1000	H 2,5/12	2224.0
	2,50	14	18	18,0	2,2	3,4	1000	H 2,5/18	3101.0
	4,00	12	9	9,0	2,8	4,0	1000	H 4,0/9	2225.0
	4,00	12	12	12,0	2,8	4,0	1000	H 4,0/12	2226.0
	4,00	12	15	15,0	2,8	4,0	1000	H 4,0/15	3102.0
	4,00	12	18	18,0	2,8	4,0	1000	H 4,0/18	3103.0
	6,00	10	12	12,0	3,5	4,7	500	H 6,0/12	2227.0
	6,00	10	15	15,0	3,5	4,7	500	H 6,0/15	2388.0
	6,00	10	15	15,0	3,5	4,7	500	H 6,0/15	3104.0
	6,00	10	18	18,0	3,5	4,7	500	H 6,0/18	3105.0
	10,00	8	12	12,0	4,5	5,8	500	H 10,0/12	2228.0
	10,00	8	15	15,0	4,5	5,8	500	H 10,0/15	2389.0
	10,00	8	18	18,0	4,5	5,8	500	H 10,0/18	2229.0
	16,00	6	12	12,0	5,8	7,5	500	H 16,0/12	2391.0
	16,00	6	15	15,0	5,8	7,5	500	H 16,0/15	2392.0
	16,00	6	18	18,0	5,8	7,5	500	H 16,0/18	2393.0
	16,00	6	25	25,0	5,8	7,5	500	H 16,0/25	3106.0
	16,00	6	32	32,0	5,8	7,5	500	H 16,0/32	3107.0
	25,00	4	15	15,0	7,3	9,5	500	H 25,0/15	2394.0
	25,00	4	18	18,0	7,3	9,5	500	H 25,0/18	2395.0
	25,00	4	25	25,0	7,3	9,5	500	H 25,0/25	3108.0
	25,00	4	32	32,0	7,3	9,5	500	H 25,0/32	3109.0
	35,00	2	18	18,0	8,3	11,0	500	H 35,0/18	2396.0
	35,00	2	25	25,0	8,3	11,0	500	H 35,0/25	3110.0
	35,00	2	32	32,0	8,3	11,0	500	H 35,0/32	3111.0
	50,00	1	18	18,0	10,3	13,0	500	H 50,0/18	3112.0
	50,00	1	25	25,0	10,3	13,0	500	H 50,0/25	3113.0
	50,00	1	32	32,0	10,3	13,0	100	H 50,0/32	2816.0
	70,00	2/0	25	25,0	12,5	15,0	100	H 70,0/25	2790.0
	70,00	2/0	32	32,0	12,5	15,0	100	H 70,0/32	3114.0
	95,00	3/0	25	25,0	14,5	17,0	50	H 95,0/25	3115.0
	95,00	3/0	32	32,0	14,5	17,0	17,0	H 95,0/32	2791.0
	120,00	4/0	MCM	32,0	16,5	19,0	50	H 120,0/32	2792.0
	150,00	300	32	32,0	18,5	21,0	50	H 150,0/32	2793.0

Końcówki nieizolowane zgodnie z DIN 46228, strona 1/3.73. Dla przewodów od 0,5-150 mm². Materiał: E-Cu, cynowane.

