

Product Range

CONTA-CON Printed circuit board terminals

Type <b>PK 550 V/H</b>  3,50 mm 7,00 mm Page 12, 21	Type <b>PK 500 V/H</b>  5,00 mm 10,00 mm 5,08 mm 10,16 mm Page 13, 14, 19, 23, 27	Type <b>PK 590</b>  5,00 mm Page 15	Type <b>PK 100 V/H</b>  5,00 mm 10,00 mm Page 16, 17, 25, 26	Type <b>PK 104 V</b>  5,00 mm Page 18
Type <b>PK 120 V/H</b>  5,08 mm Page 20	Type <b>PK 110 V/H</b>  7,50 mm Page 22	Type <b>PK 114 V</b>  7,50 mm Page 23	Type <b>PKZ 602 V</b>  3,81 mm Page 28	Type <b>PK 300</b>  5,00 mm 10,00 mm 5,08 mm 10,16 mm Page 28, 34, 42, 44
Type <b>PK 350 V</b>  5,00 mm 10,00 mm 5,08 mm 10,16 mm Page 29, 35, 43, 44	Type <b>PK 2,5</b>  5,00 mm Page 29, 35	Type <b>PK 700 V/H</b>  5,00 mm 5,08 mm Page 30, 36	Type <b>PKD 370 V</b>  5,00 mm Page 31	Type <b>PKD 750 V</b>  5,00 mm 5,08 mm Page 31, 37
Type <b>PKD 790 V</b>  5,00 mm Page 32	Type <b>PKH 793 V</b>  5,00 mm Page 32	Type <b>PKDL 2,5</b>  5,00 mm 5,08 mm Page 33, 37	Type <b>PKDR 2,5</b>  5,00 mm 5,08 mm Page 33, 38	Type <b>PK 250 V</b>  5,08 mm 10,16 mm Page 34, 43
Type <b>PKDZ 770 V</b>  5,08 mm Page 38	Type <b>PK 360 V/H</b>  7,50 mm Page 40	Type <b>PK 710 V</b>  7,62 mm Page 42	Type <b>PZK 3191</b>  2,50 mm 2,54 mm Page 46, 47	Type <b>PZK 3000, 3001</b>  5,00 mm 5,08 mm Page 48, 49
Type <b>PZK 3100, 3101</b>  5,00 mm 5,08 mm Page 51, 52	Type <b>PZK 3010, 3011, 3020, 3021</b>  7,50 mm 10,00 mm 7,62 mm 10,16 mm Page 52, 53, 54	Type <b>PZK 3750</b>  5,00 mm 5,08 mm Page 49, 50, 51	Type <b>PKT 2200 V/H</b>  5,00 mm 7,50 mm 10,00 mm Page 56, 57, 58	Type <b>PBK 4291</b>  3,50 mm Page 60
Type <b>PBK 4100</b>  5,00 mm Page 61	Type <b>PBK 4101</b>  5,00 mm Page 61	Type <b>PBK 4301</b>  5,08 mm Page 62	<p><b>Types of Connection</b></p> <ul style="list-style-type: none"> <li> Wire-protection-principle</li> <li> Tension-spring-principle</li> <li> Strain-relief-clamp-principle</li> <li> Leg-spring-principle</li> <li> Eccentric-top-principle</li> </ul>	

Product Range

CONTA-CON Printed circuit board plug-in connectors

Type <b>PKB 130</b>  5,00 mm 10,00 mm 5,08 mm 10,16 mm Page 68, 69, 70	Type <b>PKB 1550</b>  3,50 mm 3,81 mm Page 72, 73	Type <b>PKB 1550 with flange</b>  3,50 mm 3,81 mm Page 72, 73	Type <b>PKBZ 1551</b>  3,81 mm Page 74	Type <b>PKBZ 1552</b>  3,81 mm Page 74
Type <b>PKB 950</b>  5,00 mm 5,08 mm Page 75, 77	Type <b>PK 950 with flange</b>  5,00 mm 5,08 mm Page 75, 77	Type <b>PKB 1100</b>  5,00 mm 5,08 mm Page 76, 78	Type <b>PKB 1110</b>  5,00 mm 5,08 mm Page 76, 78	Type <b>PKB 960</b>  7,62 mm Page 79
Type <b>PZB 3950</b>  5,00 mm Page 80	Type <b>PBT 1200</b>  5,08 mm Page 82	Type <b>STL 130 V</b>  5,00 mm 10,00 mm 5,08 mm 10,16 mm Page 84, 85, 87	Type <b>STL 132 V</b>  5,00 mm Page 84	Type <b>STL 140 H</b>  5,00 mm 5,08 mm Page 85, 86
Type <b>STL 1550 V/H</b>  3,50 mm 3,81 mm Page 88, 90	Type <b>STL 1550 V/H with flange</b>  3,50 mm 3,81 mm Page 89, 91	Type <b>STL 1590</b>  3,81 mm Page 92	Type <b>STL 1570 V/H</b>  3,81 mm Page 93	Type <b>STL 950 V/H</b>  5,00 mm 5,08 mm Page 94, 95, 98, 99
Type <b>STL 950 V/H with flange</b>  5,00 mm 5,08 mm Page 96, 100	Type <b>STL 975 V/H</b>  5,00 mm Page 97	Type <b>STL 990</b>  5,08 mm Page 101	Type <b>STL 970 V/H</b>  5,08 mm Page 102, 103	Type <b>STL 970 V/H with flange</b>  5,08 mm Page 104
Type <b>STL 960 V/H</b>  7,62 mm Page 106, 107	Type <b>PK-TS for mounting rail TS 15, TS 32, TS 35</b>  5,08 mm Page 110	Type <b>PK-TS with flange for mounting rail TS 15, TS 32, TS 35</b>  5,08 mm Page 111	Type <b>STL 950 w. long soldering lug</b>  5,08 mm Page 117	

Types of Connection

- Wire-protection-principle
- Tension-spring-principle
- Strain-relief-clamp-principle
- Eccentric-top-principle